Shri Bajrang Ferro Alloys Co

IS A RENOWNED INDIAN MANUFACTURER OF HIGH-QUALITY FERRO ALLOYS

Shri bajrang ferro alloys co is leading ferro alloys Manufacturer from India. We are offering an extensive range of ferro alloys in various grades, sizes and forms for the use in industrial applications. We are well-known for our quality products and reliable services. Our products are highly appreciated for their superior quality and long life. We use latest technology and sophisticated machines to manufacture quality ferro alloys. We also provide customized products as per the specifications of the customers. Our team of expert professionals is always available to provide complete customer satisfaction. We have envisioned to create an inimitable name for ourselves in the domestic as well as global market by offering cost-effective ferro alloys while contributing to create a contusive environment for the industry to grow.

EMPOWERING THE WORLD WITH STRONGER ALLOYS

Shri Bajrang Ferro Alloys Co

Exporter of Ferro Alloys

Shri Bajrang Ferro Alloys Co

CONTACT US

Head Office:
Office No. 10, Opposite Bank of Baroda, Main Chowk Kanjhawala, Delhi-110081, India

+91 9899 80 4393

exports@bajrangalloys.com

https://bajrangalloys.com

PRODUCTS WE DEAL IN

FERRO SILICO MANGANESE

is a steel alloy composed of manganese, silicon, is a steel alloy composed of manganese, silicon, and iron, widely used as a deoxidizing and alloying agent to enhance the strength and quality of steel products.

FERRO CHROME

is a chromium and iron alloy that is primarily used in the production of stainless steel. It imparts excellent corrosion resistance and high-temperature strength to steel, making it ideal for various industrial applications.

HIGH CARBON FERRO MANGANESE

is an alloy made up of manganese and iron, commonly used in the steelmaking industry as a deoxidizer and alloying agent. It improves the strength, hardness, and corrosion resistance of steel.

WHO WE ARE

Shri Bajrang Ferro Alloys Co is a renowned Indian exporter of high-quality ferro alloys, with our headquarters located in Delhi, India. With a strong commitment to excellence and a rich history in the industry, we have been supplying premium ferro alloys to our valued clients since our inception. At Shri Bajrang Ferro Alloys Co, we take pride in offering a diverse range of superior ferro alloys that cater to the diverse needs of our global clientele. Our extensive product portfolio includes various types of ferro alloys, meticulously produced to meet international quality standards. We employ state-of-the-art manufacturing processes and adhere to strict quality control measures, ensuring that our products consistently meet or exceed customer expectations.

Our team of highly skilled professionals possesses extensive industry knowledge and expertise. They work diligently to provide customized solutions to our clients, catering to their specific requirements. We believe in forging strong, long-term relationships with our customers, built on trust, reliability, and exceptional service.

Shri Bajrang Ferro Alloys Co

EMPOWERING THE WORLD WITH STRONGER ALLOYS

OUR PRODUCTS SPECIFICATIONS

We set the discipline that applies engineering, physics, engineering mathematics, and materials science principles to design, analyze, manufacture, and maintain mechanical systems.

Ferro Silico Manganese (SiMn)	Mn %	Si %	C %	P %	S %	Size
SiMn 40/10	40 min	10 min	3 max	0.35 max	0.05 max	10-60 or as required
SiMn 60/14	60 min	14 min	2.5 max	0.30 max	0.03 max	10-60 or as required
SiMn 65/16	65 min	16 min	2.0 max	0.25 max	0.03 max	10-60 or as required

Ferro Manganese HC (FeMn)	Mn %	Si %	C %	P %	S %	Size
FeMn (Mn 70% min)	70 min	1.5 max	8 max	0.30 max	0.03 max	10-60 or as required
FeMn (Mn 73% min)	73 min	1.5 max	8 max	0.30 max	0.03 max	10-60 or as required
FeMn (Mn 75% min)	75 min	1.5 max	8 max	0.15 & 0.25 max	0.03 max	10-60 or as required

Ferro Chrome (FeCr)	Cr %	Si %	C %	P %	S %	Size
Ferro Chrome HC (FeCr HC)	60 min	4 max	8 max	0.04 max	0.04 max	25-150 or as required
Ferro Chrome LC (FeCr LC)	60 min	1 max	0.1 max	0.03 max	0.03 max	10-60 or as required